



Sony Xperia XA Back Cover Replacement

How to take off the back cover on a Sony Xperia XA.

Written By: Anthony Hernandez



INTRODUCTION

You will need to use a source of heat. You may need to buy adhesive for the reassembly. Make sure the phone is completely powered off before opening the device.

TOOLS:

- [Heat Gun](#) (1)
 - [Suction Handle](#) (1)
 - [iFixit Opening Tools](#) (1)
-

Step 1 — Back Cover




- Apply heat on the back surface of the phone.
- ⓘ Continue to heat the device as needed throughout the replacement process.
- ⚠ The device can get very hot, so be careful when handling it.

Step 2



- Stick the small suction cup on the bottom half of the back surface of the phone.

Step 3




- With the bottom of the device facing you, lift up on the suction cup handle.
- Use the plastic opening tool around all sides to pry off the back cover.

Step 4




- Pull the back of the phone case away from the device.
- i* You will hear popping sounds of glue being ripped from the phone.
- i* You will hear the sound of the back unlatching from the device.
- ★* You will need to apply adhesive or glue along the device to have maximum seal in reassembly.
- i* RAF antenna may be attached to the back cover upon removal.

Step 5



- Apply heat to the copper RAF antenna.
- ⓘ This step and the following step only apply if the RAF antenna does not come off when taking the back cover off.

Step 6



- Peel back the RAF antenna.

To reassemble your device, follow these instructions in reverse order.