




Dell Precision 5520 Battery Replacement

How to remove and replace the battery for the Dell Precision 5520 laptop.

Written By: Johnathan Hammond



INTRODUCTION

This guide shows how to remove and replace the battery for the Dell Precision 5520 laptop.

For your safety, discharge your battery below 25% before disassembling your device. This reduces the risk of a dangerous thermal event if the battery is accidentally damaged during the repair. If your battery is swollen, [take appropriate precautions](#).



TOOLS:


- [T5 Torx Screwdriver](#) (1)
- [Phillips #0 Screwdriver](#) (1)



PARTS:


- [Dell H5H20 56 Wh Replacement Battery](#) (1)
- [Dell 6GTPY 97 Wh Replacement Battery](#) (1)

Step 1 — Base Cover



- i** Be sure to power off and unplug your device before you begin your repair.
- Turn the system badge flap over (1) and then remove the ten M2x3 screws that secure the base cover to the computer (2).
 - Pry the edges of the base cover and lift it to remove it from the computer.
- i** NOTE: Use a Torx #5 screwdriver for the base screws and a Phillips screwdriver for the two M2x8 screws inside the badge flap.

Step 2 — Battery



- Disconnect the battery cable from the system board [1].
- Remove the seven M2x4 screws that secure the battery to the computer [2].
- Lift the battery off the computer [3].

⚠ Do not apply pressure to the surface of the battery

⚠ Do not bend

⚠ Do not use tools of any kind to pry on or against the battery

ⓘ If a battery cannot be removed within the constraints above, please contact Dell technical support

To reassemble your device, follow these instructions in reverse order.

Take your e-waste to an [R2 or e-Stewards certified recycler](#).

Repair didn't go as planned? Try some [basic troubleshooting](#), or ask our [Answers community](#) for help.