



Samsung LNT4669FX-XAA TV Power Supply Board Replacement

How to replace the Power Supply Board in the Samsung LNT4669FX-XAA TV when the TV is not powering on and you don't want change electronic components.

Written By: James Finch



INTRODUCTION

I was given a free Samsung Television model LNT4669FX-XAA that wouldn't power on that I found on offerup.com.

I've found other free TV's on craigslist.org, letgo.com and other online sites. These are good sources of electronics to practice on if you are a student, hobbyist or whatever compels you to save some electronics from going into the junk yard. Enough of the electronics restore, repair, re-use and recycling advocacy.

The gentleman that gave me the TV noted that his father had tried to repair the TV before and it worked for a day. He wasn't sure what his father had worked on.

When I brought the TV home and plugged in, I found it did nothing.

I took off the back cover and found a blown fuse and an assortment of new capacitors that I wasn't sure were even in specification.

I decided for the price of a new board, I'd buy a new board (found for ~\$20) off eBay and try repairing the old board later with a Shopjimmy.com board repair kit.

I replaced the power supply board and the TV is performing up to specification from what I can tell now.

TOOLS:

- [Phillips #3 Screwdriver](#) (1)

PARTS:

- [Samsung INT4669FX-XAA TV Power Supply Board](#) (1)

Step 1 — Remove back cover screws



- Be sure to unplug the TV from the main wall outlet.
- Carefully lay the TV screen down on a clean flat table with the back side facing you.
- Using a #3 Phillips head screwdriver, remove the screws holding the back cover on.
- Thoroughly clean the cover and boards using a damp towel (I like to use 91% isopropyl alcohol) and if heavily soiled use a vacuum with a brush.

Step 2 — Remove Power Supply Board



- Using the #3 Phillips head screwdriver, remove the screws holding the power supply board on.
- Unplug the connectors connected to the board setting aside and carefully noting placement for later connection to the new board.

Step 3 — Install the new Power Supply Board



- Insert the new power supply board into the location where the old board was located.
- Follow the previous steps to connect the cables and screw in the screws.

Step 4 — Install the back cover



- Follow the first step in reverse to install the back cover.

Step 5 — Power on the TV to test performance



- Plug the power cord into a wall outlet and power on the TV to verify performance.

To reassemble your device, follow these instructions in reverse order.

You can also repair your Power Supply Board potentially by using the BN44-00166C repair kit.

See the Attached Documents schematic for further Power Supply Board details.