



# Toshiba Satellite A105-S4011 Keyboard Replacement

Replace the keyboard of your Toshiba A105.

Written By: Lucas Salisbury



---

## INTRODUCTION

Replacing the keyboard will require some prying, but it does not take too many steps. (Note that the last step in this guide is not necessary to remove the keyboard, but IS necessary if you later would like to disconnect the display piece from the rest of laptop.)

---

### TOOLS:

- [Phillips #00 Screwdriver](#) (1)  
*(or wedge prying tool)*
  - [Phillips #1 Screwdriver](#) (1)
-

## Step 1 — Keyboard



- i Make sure to turn off the laptop, unplug the device and/or remove any batteries.
- Open the laptop so the display screen is bent fully back with the display facing upward, parallel to the surface you are working on.
- Wedge the Phillips 00 screwdriver above the F1 key, and separate the top piece of plastic from the body of the laptop. Don't worry about breaking it! You will need to forcefully wedge the screwdriver under the plastic, simultaneously pushing upward and forward.
- Once that section has popped up, work on pulling the rest of the plastic piece up and out, alternating from left to right.

## Step 2



- Completely remove the plastic piece from the body of the laptop.
- Using the Phillips 1 screwdriver, unscrew the two 3mm screws located at the top corners of the keyboard. (See the second picture for additional clarification.)

### Step 3



- Without yanking, lift the keyboard up carefully.
- Now that the board is free, cautiously undo and pull free the ribbon that connects the keyboard to the body of the laptop.

To reassemble your device, follow these instructions in reverse order.