



HP iPAQ h4155 Face Plate Replacement

Written By: John Pagliero



TOOLS:

T5 Torx Screwdriver (1)

Tweezers (1)

Phillips #00 Screwdriver (1)

iFixit Opening Tool (1)

Step 1 — Battery



- While sliding the silver release tab up, simultaneously lift the cover up from the left side.

Step 2



- Push the tab left to right to remove the cover.

Step 3



- Now, lift the battery up and away from the device to remove it.

Step 4 — Back Case



- Remove the four silver screws using the T5 Torx Screwdriver (T5 x .25 in).

Step 5



- Remove the single black screw that is located beneath the HP sticker with the T5 Torx Screwdriver.

Step 6



- Next, use your plastic removal tool to separate the gray back from the black center piece.
- For better results, start the separation at the corner piece.

Step 7





- Remove the back case.

Step 8 — Face Plate



- Now that the back cover is removed, use the #00 Philips x .17 screwdriver to remove the small screw to the left of the SD card slot.


Step 9



- Next, unlock and remove the ribbon cable.
- Using metal [tweezers](#), carefully pull back on both sides of the brown bar unlocking the cable and slipping it out of the connector.


⚠ The bar, the connector, and the cable are fragile components that are easily broken.

Step 10



- Next, remove the wire from the bottom of the mother board.
- ① The easiest method is to use metal tweezers and grip the plug closest to the connector.
- Make sure all the connections are properly disconnected before separation from the motherboard.

Step 11



- Next, use a plastic removal tool and separate the silver front case from the black frame.

To reassemble your device, follow these instructions in reverse order.